



537 060
 Naturally Oiled Oak

537 054
 Smokey Oak

537 412
 Tavern Oak

537 005
 Country Squire

537 047
 Arctic Oak

537 048
 Nickel Finished Oak

537 006
 Espresso Oak

537 824
 Cabin Multi-strip

Size
 7" x 48" nominal (18 cm x 122 cm)
 5.0 mm thick

Wear Layer
 12 mil / UV-Cured Urethane

Edge Treatment
 Four-Sided Micro-Bevel

Installation
 Click Floating Floor Angle-Angle
(on, above or below grade)

Attached Cushion
 For superior sound abatement
 and easier installation

Coordinating Moldings
 See nextfloor.net for more details.

Packaging
 12 pieces per carton (43 lbs)
 28.4 SF per carton
 55 cartons per pallet
 18 pallets per container

Testing
 Critical Radiant Flux
 Surface Flammability
 Coefficient of Friction
 Static Load Limit
 Sound Transmission Class (STC)
 Impact Insulation Class (IIC)
 High Frequency Impact Insulation Class(HIIC)
 Floor Score Certified
 Phthalate Free
 100% Virgin PVC

Warranties
 Lifetime Waterproof
 Lifetime Residential Wear
 10-Year Commercial Wear*
 *For moderate traffic areas without rolling loads, heavy
 fixtures or ramps. See full warranty text at nextfloor.net

ASTM E648	Class I
DOC FF 1-70	Passed
ASTM 2047	Passes >0.6
ASTM F970	exceeds 3000 lbs <small>without cushion</small>
ASTM E492	64
ASTM E989	71
ASTM E3222	88



Sample SKUs

Handle Boards
 HB537NF-C
 5 per carton (63 lbs)

Strap Sets
 SS537NF-C
 5 per carton (37.5 lbs)

Step Up Display
 4CARDS537NF-1C
 (006, 047, 048, 012)
 4CARDS537NF-2C
 (054, 060, 005, 824)
 FIXT537NF
 Packaged in 3 cartons (165 lbs)

