

Coastal Resort 439 Heavy Commercial Traffic



439 051
Mineral White Maple



439 026
Dovetail Gray




439 005
Aged Driftwood



439 002
Light Twine



439 043
Salted Caramel



439 011
Shaded Walnut

Size

7.25" x 48" x 2.5 mm

Wear Layer

20 mil / UV-Cured Urethane

Embossing

Real Touch™ Embossed in Register

Edge Treatment

Beveled

Installation

Full Spread Adhesive
Recommended Adhesive: NEXT 1200™

Packaging

17 pieces per carton (40 lbs)
41.1 SF per carton
55 cartons per pallet
20 pallets per container

Coordinating Moldings

See nextfloor.net for more details.

Testing

Critical Radiant Flux
Surface Flammability
Coefficient of Friction
Static Load Limit
Sound Transmission Class (STC)
Impact Insulation Class (IIC)
High Frequency Impact Insulation Class(HIIC) ASTM E322
Floor Score Certified
Phthalate Free
100% Virgin PVC



ASTM E648 Class I
DOC FF 1-70 Passed
ASTM 2047 Passes>0.6
ASTM F970 1300 lbs
ASTM E492 64
ASTM E989 69
89

Product Classification

ASTM F1700 Class III, Type B

Warranties

Lifetime Waterproof
Lifetime Residential Wear
25-Year Commercial Wear*
**See full warranty text at nextfloor.net*

Sample SKUs

Handle Boards

HB439NF-C
5 per carton (43 lbs)

Strap Sets

SS439NF
5 per carton (19 lbs)

Folders

3P439NF-C
20 per carton (56 lbs)

