

# Donnington 450



450 545  
Natural Oak



450 503  
Vanilla Hickory



450 508  
Heritage Oak



450 544  
Mocha Oak



450 500  
Modern Hickory



450 543  
Silver Oak

## Size

9.25" x 60.25"  
4.5 mm thick

## Wear Layer

20 mil / UV-Cured Urethane

## Edge Treatment

4-Sided Micro-bevel

## Installation

DropFit Loose Lay with perimeter adhesive  
or Full Spread Adhesive

See installation instructions at [nextfloor.net](http://nextfloor.net)

## Recommended Adhesive

NEXT 1200™

## Construction

DropFit Loose Lay with  
Fibreglass Reinforcement

## Packaging

6 pieces per carton (41 lbs)  
23.22 SF per carton  
60 cartons per pallet  
18 pallets per 20ft container

## Testing

Critical Radiant Flux  
Surface Flammability  
Coefficient of Friction  
FloorScore Certified  
Phthalate Free  
100% Virgin Material

## Warranties

Lifetime Waterproof  
Lifetime Residential Wear  
20-Year Commercial Wear

See full warranty text at [nextfloor.net](http://nextfloor.net)

ASTM E648  
DOC FF 1-70  
ASTM 2047

Class I  
Passed  
Passed>0.6



## Sample SKUs

### Strap Sets

SS450NF  
5 per carton (36 lbs)

### Hanging Display

PL450NF  
6 planks per carton (50 lbs)  
**Two cartons of PL450NF  
per display**  
HSFIXT450NF  
1 per carton (42 lbs)



# Donnington 450 Display

