Donnington 450



Size 9.25" x 60.25" 4.5 mm thick

Wear Layer 12 mil / UV-Cured Urethane

Edge Treatment 4-Sided Micro-bevel

Installation DropFit Loose Lay with perimeter adhesive or Full Spread Adhesive

See installation instructions at nextfloor.net

Recommended Adhesive NEXT 1200™

Construction DropFit Loose Lay with Fibreglass Reinforcement

Packaging

6 pieces per carton (44 lbs) 23.22 SF per carton 60 cartons per pallet 18 pallets per 20ft container

Testing

Critical Radiant Flux Surface Flammability Coefficient of Friction Floor Score Certified Phthalate Free 100% Virgin Material

Warranties Lifetime Waterproof Lifetime Residential Wear 20-Year Commercial Wear See full warranty text at nextfloor.net ASTM E648 DOC FF 1-70 ASTM 2047



Class I Passed Passed>0.6



Sample SKUs

5 per carton (36 lbs)

Strap Sets

SS450NF





nextfloor.net 09.11.23

Donnington 450





450 543 Silver Oak

Size 9.25" x 60.25" 4.5 mm thick

Wear Layer 12 mil / UV-Cured Urethane

Edge Treatment 4-Sided Micro-bevel

Installation DropFit Loose Lay with perimeter adhesive or Full Spread Adhesive

See installation instructions at nextfloor.net

Recommended Adhesive NEXT 1200™

Construction DropFit Loose Lay with Fibreglass Reinforcement

Packaging

6 pieces per carton (44 lbs) 23.22 SF per carton 60 cartons per pallet 18 pallets per 20ft container

ASTM E648

DOC FF 1-70

ASTM 2047

Class I

Passed

Passed>0.6

Testing

Critical Radiant Flux Surface Flammability Coefficient of Friction Floor Score Certified Phthalate Free 100% Virgin Material

Warranties Lifetime Waterproof Lifetime Residential Wear 20-Year Commercial Wear See full warranty text at nextfloor.net Sample SKUs

Strap Sets SS450NF 5 per carton (36 lbs)

Hanging Display PL450NF 6 planks per carton (50 lbs) Two cartons of PL450NF per display HSFIXT450NF 1 per carton (42 lbs)





nextfloor.net 09.11.23