Available in Two Formats: WPC Click Floating Floor & Glue Down LVT





Epic 586 WPC Specifications

Size

7" x 48" nominal (18 cm x 122 cm) 7.0 mm thick

Construction

5-Layer WPC

Wear Layer

20 mil / UV-Cured Endurium™ Enhanced Urethane Protection

Edge Treatment

Four-Sided Color-Enhanced Bevel

Installation

Click Floating Floor, Angle Angle (on, above or below grade)

Attached Cushion

For superior sound abatement and easier installation

Coordinating Moldings

See nextfloor.net for more details.

Packaging

12 pieces per carton (43 lbs) 28.4 SF per carton 55 cartons per pallet 20 pallets per 20ft container

Testing

Critical Radiant Flux Surface Flammability Coefficient of Friction Floor Score Certified Phthalate Free 100% Virgin PVC

Warranties

Lifetime Waterproof Lifetime Residential Wear Lifetime No Cupping* 30-Year Commercial Wear† ASTM E648

DOC FF 1-70

ASTM D2047

Class I

Passed

Passed>0.6

For glue down specifications, see fact sheets for Indestructible Plus 415, Coastal Resort 439 and Colorado 417 at nextfloor.net.

Sample SKUS

Handle Boards HB586NF 5 per carton (67 lbs)

Strap Set SS586NF 5 per carton (67 lbs)

Step Up Display 8CARDS586NF-1 (713, 705, 043, 117) 8CARDS586NF-2 (118, 002, 005, 110) FIX586NF Packaged in 3 cartons (150 lbs)

Wing Rack Update

WING8CARDS586NF-1 (713, 705, 043, 117) WING8CARDS586NF-2 (118, 002, 005, 110) 1WINGNF-GRAY (EXTRA WING) Packaged in 3 cartons (140 lbs)



^{*}When properly installed, see full warranty text at nextfloor.net

[†]For moderate traffic areas without rolling loads, heavy fixtures or ramps.