Exceptional 539 Heavy Commercial







Size

7" x 48" *nominal* (18 cm x 122 cm) 5.5 mm thick

Wear Layer

20 mil / UV-Cured Urethane

Edge Treatment

Enhanced Bevel

Installation

Drop Lock, Click Floating Floor (on, above or below grade)

Attached Cushion

For superior sound abatement and easier installation

Coordinating Moldings

See nextfloor.net for more details.

Packaging

12 pieces per carton (40 lbs) 28.4 SF per carton 55 cartons per pallet 18 pallets per container

Testing

Critical Radiant Flux ASTM E648 Class I Surface Flammability DOC FF 1-70 Passed Coefficient of Friction ASTM 2047 Passes>0.6 ASTM F970 exceeds 3000 lbs Static Load Limit Sound Transmission Class (STC) ASTM E492 64 Impact Insulation Class (IIC) ASTM E989 71 High Frequency Impact Insulation Class(HIIC) ASTM E3222 88 Floor Score Certified Phthalate Free 100% Virgin PVC

Warranties

Lifetime Waterproof Lifetime Residential Wear 20-Year Commercial Wear*

*For moderate traffic areas without rolling loads, heavy fixtures or ramps. See full warranty text at nextfloor.net

Sample SKUs

Handle Boards HB539NF 10 per carton (126 lbs) 539 016

Taupestone (Planks Vary)

Strap Sets SS539NF 5 per carton (37.5 lbs)

Step Up Display 8CARDS539NF-1 8CARDS539NF-2 FIXT539NF

Packaged in 3 cartons (165 lbs)



