

Groundwork 423 & Bedrock 424 Commercial Traffic



Size

Plank 423 7.25" x 48"
2 mm thick

Tile 424 12" x 24"
2 mm thick

Wear Layer

12 mil / UV-Cured Urethane

Edge Treatment

Square Edge

Installation

Full Spread Adhesive
Recommended Adhesive: NEXT 1200™

Product Classification

ASTM F1700 Class III, Type B

Coordinating Moldings

See nextfloor.net for more details.

Packaging

Plank 21 pieces per carton (45 lbs)
50.8 SF per carton
55 cartons per pallet
20 pallets per container

Tile 27 pieces per carton (45 lbs)
54 SF per carton
54 cartons per pallet
20 pallets per container

Testing

Critical Radiant Flux	ASTM E648	Class I
Surface Flammability	DOC FF 1-70	Passed
Coefficient of Friction	ASTM D2047	Passes > 0.6
Static Load Limit	ASTM F970	1300 lbs
Floor Score Certified		
Phthalate Free		
100% Virgin PVC		

Warranties

20-Year Waterproof
20-Year Residential Wear
10-Year Commercial Wear

See full warranty text at nextfloor.net

Sample SKUs

Handle Boards
HB424NF-B
5 per carton (40 lbs)

Strap Sets
SS424NF-B
5 per carton (20 lbs)

Folders
3P424NF-B
10 per carton (32 lbs)

