

# Level Best 433 Extra Heavy Commercial Traffic



**Size**  
7.25" x 48" nominal (18.5 cm x 122 cm)  
5 mm thick

**Wear Layer**  
28 mil / UV-Cured Urethane  
MCX™ MicroCeramic Reinforced Resin

**Embossing**  
Real Touch™ Embossed in Register

**Edge Treatment**  
Four-Sided Microbevel

**Installation**  
Full Spread Adhesive  
Recommended Adhesive: NEXT 1200™

**Coordinating Moldings**  
See [nextfloor.net](http://nextfloor.net) for more details.

**Packaging**  
9 pieces per carton (40 lbs)  
21.8 SF per carton  
50 cartons per pallet  
20 pallets per container

**Testing**

Critical Radiant Flux	ASTM E648	Class I
Surface Flammability	DOC FF 1-70	Passed
Coefficient of Friction	ASTM 204	Passes>0.6
Static Load Limit	ASTM F970	1200 lbs
Sound Transmission Class (STC)	ASTM E492	62
Impact Insulation Class (IIC)	ASTM E989	57
High Frequency Impact Insulation Class(HIIC)	ASTM E3222	89

Floor Score Certified  
Phthalate Free  
100% Virgin PVC



**Warranties**  
Lifetime Waterproof  
Lifetime Residential Wear  
40-Year Commercial Wear  
Lifetime Transition Integrity\*  
\*When installed beside Next Floor nylon carpet tile.  
See full warranty text at [nextfloor.net](http://nextfloor.net)

## Sample SKUs

**Handle Boards**  
HB433NF  
*\*includes Bandwidth Carpet  
10 per carton (110 lbs)*

**Strap Sets**  
SS433NF  
*5 per carton (36 lbs)*

**Folders**  
2P433NF  
*\*includes Bandwidth Carpet  
20 per carton (60 lbs)*

## Extra Heavy Duty LVT

- 5 mm total thickness
- 28 mil wear layer
- MCX™ MicroCeramic protection
- 40-Year Commercial Warranty