

Marvelous Plus 425 Extra Heavy Commercial LVT



Size

7.25" x 48"
3 mm thick

Wear Layer

28 mil / UV-Cured Urethane
MCX™ MicroCeramic Reinforced Resin

Embossing

Realistic Texture
Embossed in Register

Edge Treatment

Beveled

Installation

Full Spread Adhesive
Recommended Adhesive:
NEXT 1200™

Packaging

14 pieces per carton (40 lbs)
33.8 SF per carton
55 cartons per pallet
20 pallets per container

Testing

Critical Radiant Flux	ASTM E648	Class I
Surface Flammability	DOC FF 1-70	Passed
Coefficient of Friction	ASTM 2047	Passed>0.6
Static Load Limit	ASTM F970	1300 lbs
Sound Transmission Class (STC)	ASTM E492	64
Impact Isulation Class (IIC)	ASTM E989	69
High Frequency Impact Isulation Class(HIIC)	ASTM E3222	89

Floor Score Certified
Phthalate Free
100% Virgin PVC



Product Classification

ASTM F1700 Class III, Type B

Warranties

Lifetime Waterproof
Lifetime Residential Wear
30-Year Commercial Wear
See full warranty text at nextfloor.net

Coordinating Moldings

See nextfloor.net for more details.

Sample SKUs

Handle Board

HB425NF
5 per carton (40 lbs)

Folder

3P425NF
10 per carton (30 lbs)