

Tuscan Sandstone Heavy Commercial Traffic



Size
12" x 24" nominal (31 cm x 62 cm)
2.5 mm thick

Wear Layer
20 mil / UV-Cured Urethane

Edge Treatment
Four-Sided Microbevel

Product Classification
ASTM F1700 Class III, Type B

Installation
Full Spread Adhesive
NEXT 1200™ recommended
With or without grout
Mapei Flexcolor CQ recommended

Coordinating Moldings
See nextfloor.net for more details.

Packaging
21 pieces per carton (39 lbs)
42 SF per carton
54 cartons per pallet
20 pallets per container

Testing

Critical Radiant Flux	ASTM E648	Class I
Surface Flammability	DOC FF 1-70	Passed
Coefficient of Friction	ASTM 2047	Passes > 0.6
Static Load Limit	ASTM F970	1300 lbs
Sound Transmission Class (STC)	ASTM E492	64
Impact Isulation Class (IIC)	ASTM E989	69
High Frequency Impact Isulation Class (HIIC)	ASTM E3222	89
Floor Score Certified		
Phthalate Free		
100% Virgin PVC		



Warranties
Lifetime Waterproof
Lifetime Residential Wear
25-Year Commercial Wear*
*See full warranty text at nextfloor.net

Sample SKUs

Handle Boards
HB446NF
5 per carton (50 lbs)

Strap Sets
SS446NF
5 per carton (45 lbs)

Folders
3P446NF-C
10 per cartons (30 lbs)

