

Patina 419 Extra Heavy Commercial Traffic



Size

18" x 24" x 3 mm thick

Wear Layer

28 mil / UV-Cured Urethane

Edge Treatment

Beveled

Installation

Full Spread Adhesive

Recommended Adhesive: NEXT 1200™

Packaging

11 pieces per carton (40 lbs)

33 SF per carton

60 cartons per pallet

20 pallets per container

Coordinating Moldings

See nextfloor.net for more details.

Testing

Critical Radiant Flux

Surface Flammability

Coefficient of Friction

Static Load Limit

Sound Transmission Class (STC)

Impact Isulation Class (IIC)

High Frequency Impact Isulation Class(HIIC)

Floor Score Certified

Phthalate Free

100% Virgin PVC



ASTM E648 Class I

DOC FF 1-70 Passed

ASTM 2047 Passes>0.6

ASTM F970 1300 lbs

ASTM E492 64

ASTM E989 69

ASTM E3222 89

Sample SKUs

Handle Boards

HB419NF

5 per carton (50 lbs)

Folders

3P419NF

20 per carton (64 lbs)

Product Classification

ASTM F1700 Class III, Type B

Warranties

Lifetime Waterproof

Lifetime Residential Wear

30-Year Commercial Wear

See [full warranty text at nextfloor.net](http://fullwarrantytextatnextfloor.net)

